

**PART 1 SPECIFICATIONS**

Technical parameters	Technical parameters	Technical parameters	Technical parameters
Item No.	<b>S-218</b>	<b>S-18</b>	<b>S-15</b>
System Type	Ultra-low Sub bass,passive	Ultra-low Sub bass,passive	Ultra-low Sub bass,passive
Frequency Response (±3 dB)	30- 400 Hz	32- 400 Hz	45- 400 Hz
Nominal Impedance	4 Ω	8 Ω	8 Ω
System sensitivity	102 dB	99 dB	95 dB
Power Rating (Continuous)	1200 W	600 W	350 W
Power Rating ( Peak)	4800W	2400W	1400W
Maximum SPL	139 dB	133 dB	126 dB
Coverage Pattern	—	—	—
Crossover Mode	external crossover	external crossover	external crossover
<b>Product Features</b>	<b>Product Features:</b>	<b>Product Features:</b>	<b>Product Features:</b>
HF Driver	—	—	—
MF Driver	—	—	—
LF Driver	18" x2, ferrite magnet Ø220 mm / 8.8 in; voice coil Ø100 mm / 4 in made of aluminium wire; high density cast aluminium alloy frame	18" x2, ferrite magnet Ø220 mm / 8.8 in; voice coil Ø100 mm / 4 in made of aluminium wire; cast aluminium alloy frame	15" x2, ferrite magnet Ø220 mm / 8.8 in; voice coil Ø100 mm / 4 in made of aluminium wire; cast aluminium alloy frame
Input Connectors	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2
Output Connectors	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2
Enclosure	18mm Birch plywood	18mm Birch plywood	18mm Birch plywood
Grille	ferrite,foam backing	ferrite,foam backing	ferrite,foam backing
Finish	Black catalyzed polyurethane paint	Black catalyzed polyurethane paint	Black catalyzed polyurethane paint
Suspension / Mounting	—	—	—
Colour	black	black	black
Product Dimensions(mm,inch)	1070W×780 D×565 H /42.8x 31.2 x22.6 in	560W×595 D×695 H 22.4x 23.8 x27.8 in	471W×500 D×684 H/ 18.842.4x 25 x29.36n
Package Dimensions(mm,inch)	1110W×820 D×630 H /44.4x 32.8x 25.2 in	650W×620 D×750 H /26x 24.8x 30 in	550W×520 D×740 H /22x 20.8 x 29.6 in
Net Weight(kgs,lbs)	74 KGS/ 163.26 lbs	43 KGS/ 94.87 lbs	28 KGS/61.78 lbs
Gross Weight(kgs,lbs)	82 KGS/ 180.91 lbs	46 KGS/ 101.49lbs	30.5 KGS/ 67.29 lbs
Optional Accessories			
Package Rate(pc/carton)			
PCS/20" FCL/40"FCL/40"HQ	50/101/132	95/191/251	137/274/359
<b>Operating the System</b>	<b>Operating the System:</b>	<b>Operating the System:</b>	<b>Operating the System:</b>
Recommended Amplification	1500 - 1800 Watt @4 ohms 1 x amplifier	750 - 900 Watt @8 ohms 1 x amplifier	450 -550Watt @8 ohms 1 x amplifier
Subwoofer Options			
System Controller			
Speaker Cables			