

PART 1 SPECIFICATIONS

Technical parameters	Technical parameters:	Technical parameters:
Item No.	KS-420	KS-10
System Type	2-WAY full range	3-WAY full range
Frequency Response (±3 dB)	45- 18k Hz	40- 18k Hz
Nominal Impedance	8Ω	8Ω
System sensitivity	95 dB	95 dB
Power Rating (Continuous)	300 W	250 W
Power Rating (Peak)	600W	600W
Maximum SPL	123 dB	122 dB
Coverage Pattern	—	—
Crossover Mode	internal crossover	internal crossover
Product Features	Product Features:	Product Features:
HF Driver	3" x4, ferrite magnet Ø220 mm / 8.8 in; voice coil Ø14 mm / 0.56 in	3" x2, ferrite magnet Ø60 mm / 2.4 in; voice coil Ø14 mm / 0.56 in
MF Driver	—	3" x1, ferrite magnet Ø60 mm / 2.4 in; voice coil Ø14 mm / 0.56 in
LF Driver	10" x1, ferrite magnet Ø156 mm /6.24 in; voice coil Ø65 mm / 2.6 in	10" x1, ferrite magnet Ø120 mm /4.8 in; voice coil Ø50 mm / 2 in; iron frame
Input Connectors	line box	line box
Output Connectors	line box	line box
Enclosure	15mm MDF	15mm MDF
Grille	ferrite,foam backing	ferrite,foam backing
Finish	Black catalyzed polyurethane paint	Black catalyzed polyurethane paint
Suspension / Mounting	—	—
Colour	black	black
Product Dimensions(mm,inch)	516W×335 D×302 H /20.64x 13.4 x12.08 in	520W×320 D×300 H /20.8x 12.8 x12. in
Package Dimensions(mm,inch)	790W×575 D×370 H /31.6x 23x 14.8in	752W×370 D×595 H /30.08x 14.8x 23.8in
Net Weight(kgs,lbs)	13.2 KGS/ 29.12 lbs	14.5 KGS/ 31.99 lbs
Gross Weight(kgs,lbs)	29 KGS/ 63.98 lbs	32 KGS/ 70.6 lbs
Optional Accessories		
Package Rate(pc/carton)		
PCS/20" FCL/40"FCL/40"HQ	172/345/452	175/350/459
Operating the System	Operating the System:	Operating the System:
Recommended Amplification	350 - 450 Watt @8 ohms 1 x amplifier	300 - 400 Watt @8 ohms 1 x amplifier
Subwoofer Options		
System Controller		
Speaker Cables		