

PART 1 SPECIFICATIONS

| Technical parameters | Technical parameters: | Technical parameters: |
|-----------------------------|--|--|
| Item No. | F-215 | F-15 |
| System Type | 2-WAY full range,passive | 2-WAY full range,passive |
| Frequency Response (±3 dB) | 35Hz-18k Hz | 43Hz-18k Hz |
| Nominal Impedance | 4 Ω | 8 Ω |
| System sensitivity | 101 dB | 98 dB |
| Power Rating (Continuous) | 800 W | 450 W |
| Power Rating (Peak) | 3200W | 1800W |
| Maximum SPL | 136 dB | 131 dB |
| Coverage Pattern | 80° x 50° | 80° x 50° |
| Crossover Mode | internal crossover | internal crossover |
| Product Features | Product Features: | Product Features: |
| HF Driver | 2" x1, ferrite magnetØ120mm / 6.8 in; voice coilØ44 mm / 1.76 in of Flat copper wire | 2" x1, ferrite magnetØ120mm / 6.8 in; voice coil Ø44 mm/1.76 in of Flat copper wire |
| MF Driver | — | — |
| LF Driver | 15" x2,compression driver ferrite magnetØ170mm / 7.6 in; voice coil Ø75 mm / 3 in made of flat | 15" x1,compression driver ferrite magnetØ170mm / 7.6 in; voice coilØ75mm / 3 in made of flat aluminium |
| Input Connectors | NL4speakon(x2) NL4socketx2 | NL4speakon(x2) NL4socketx2 |
| Output Connectors | NL4speakon(x2) NL4socketx2 | NL4speakon(x2) NL4socketx2 |
| Enclosure | 18mm MDF | 18mm MDF |
| Grille | ferrite | ferrite |
| Finish | Black catalyzed polyurethane paint | Black catalyzed polyurethane paint |
| Suspension / Mounting | multiple-point suspension /floor stands | multiple-point suspension /floor stands |
| Colour | black | black |
| Product Dimensions(mm,inch) | 560W×500D×1216H /22.4 x 20 x 48.64 in | 475W×445D×685H /19 x17.8 x 27.4 in |
| Package Dimensions(mm,inch) | 625W×563D×1300H /25x 22.52 x 52 in | 530W×505D×750H /21.2x 20.2 x 30 in |
| Net Weight(kgs,lbs) | 52 KGS/ 114.73lbs | 26.5 KGS/ 58.47lbs |
| Gross Weight(kgs,lbs) | 54.5 KGS /120.24 lbs | 28.5 KGS /62.88 lbs |
| Optional Accessories | aluminium alloy suspension fittings | aluminium alloy suspension fittings |
| Package Rate(pc/carton) | | |
| PCS/20" FCL/40"FCL/40"HQ | 63/126/166 | 144/288/378 |
| Operating the System | Operating the System: | Operating the System: |
| Recommended Amplification | 960 - 1200 Watt @ 4 ohms 1 x amplifier | 550 - 700 Watt @ 8 ohms 1 x amplifier |
| Subwoofer Options | | |
| System Controller | | |
| Speaker Cables | | |