

## PART 1 SPECIFICATIONS

Technical parameters	Technical parameters:	Technical parameters:	Technical parameters:
Item No.	<b>HY-605</b>	<b>HY-208</b>	<b>HY-206</b>
System Type	2-WAY full range	2-WAY full range	2-WAY full range
Frequency Response (±3 dB)	60- 18k Hz	57- 18k Hz	60- 18k Hz
Nominal Impedance	8Ω	8Ω	8Ω
System sensitivity	88 dB	95 dB	88 dB
Power Rating (Continuous)	70 W	80 W	70 W
Power Rating ( Peak)	140W	160W	140W
Maximum SPL	109 dB	117 dB	109 dB
Coverage Pattern	—	—	—
Crossover Mode	internal crossover	internal crossover	internal crossover
<b>Product Features</b>	<b>Product Features:</b>	<b>Product Features:</b>	<b>Product Features:</b>
HF Driver	3" x1, ferrite magnet Ømm / 8.8 in; voice coil Ø25 mm / 1 in	1" x1, ferrite magnet Ø80 mm / 3.2in; voice coil Ø25 mm / 1 in	1" x1, ferrite magnet Ø80 mm / 3.2in; voice coil Ø25 mm / 1 in
MF Driver	—	—	—
LF Driver	6.5" x3,ferrite magnets Ø100 mm /4 in; voice coil Ø35 mm / 1.4 in	8" x1,dual ferrite magnets Ø120 mm /4.8 in; voice coil Ø35 mm / 1.4 in	6.5" x1,l ferrite magnets Ø120 mm /4.8 in; voice coil Ø35 mm / 1.4 in
Input Connectors	wire clamp	wire clamp	wire clamp
Output Connectors	wire clamp	wire clamp	wire clamp
Enclosure	12mm MDF	12mm MDF	12mm MDF
Grille	ferrite,foam backing	ferrite,foam backing	ferrite,foam backing
Finish	black catalyzed polyurethane paint	black catalyzed polyurethane paint	black catalyzed polyurethane paint
Suspension / Mounting	multiple-point suspension	multiple-point suspension	multiple-point suspension
Colour	black	black	black
Product Dimensions(mm,inch)	301W×176 D×209 H /12.04x 7.04 x8.36 in	247W×255 D×410 H /9.88x 10.2 x16.4 in	208 W×235 D×365 H /8.32x 9.4 x14.6 in
Package Dimensions(mm,inch)	420W×240 D×360 H /16.8x 9.64x 14.4in	520W×300 D×460 H /20.8x 12x 18.4in	450 W×275 D×415 H /18x 11x 16.6in
Net Weight(kgs,lbs)	5 KGS/ 11.03 lbs	6.5KGS/ 14.34 lbs	5.3 KGS/ 11.69 lbs
Gross Weight(kgs,lbs)	KGS/ 119.25 lbs	14.2 KGS/31.33 lbs	11.6 KGS/25.59 lbs
Optional Accessories			
Package Rate(pc/carton)			
PCS/20" FCL/40"FCL/40"HQ	799/1598/2094	404/808/1059	564/1129/1479
<b>Operating the System</b>	<b>Operating the System:</b>	<b>Operating the System:</b>	<b>Operating the System:</b>
Recommended Amplification	80 -100 Watt @8 ohms 1 x amplifier	100-150 Watt @8 ohms 1 x amplifier	80-100 Watt @8 ohms 1 x amplifier
Subwoofer Options			
System Controller			
Speaker Cables			