

### PART 1 SPECIFICATIONS

	<b>Technical parameters</b>	<b>Technical parameters</b>	<b>Technical parameters</b>	<b>Technical parameters</b>	<b>Technical parameters</b>
1	MODEL	S-779	S-778	S-779F	S-778F
2	Rated output power 8Ω	450W×2	350W×2	450W×2	350W×2
3	Rated output power 4Ω	400W×2	500W×2	400W×2	500W×2
4	Frequency response	20HZ-20KHZ (+0.5, -0.5dB)			
5	Signal-to-noise ratio	89dB	86dB	86dB	86dB
6	Input sensitivity	0.45V	0.4V	0.24V	0.4V
7	THD	≤0.05%	≤0.05%	≤0.05%	≤0.05%
8	Input impedance	47KΩ	47KΩ	47KΩ	47KΩ
9	Supply power	1000W	800W	600W	800W
10	Exchange insurance	10A	8A	5A	8A
	<b>Construction description</b>	<b>Construction description</b>	<b>Construction description</b>	<b>Construction description</b>	<b>Construction description</b>
11	Rack space	3U	3U	3U	3U
12	Output circuitry	Class AB	Class AB	Class AB	Class AB
13	Input Connectors	RCA	RCA	RCA	RCA
14	Link Connectors				
15	Output Connectors	binding post	binding post	binding post	binding post
16	Cooling	constant speed	constant speed	constant speed	constant speed
17	Indicators				
18	Protection	short-circuit,DC voltage, thermal, over load, limiter			
19	Power Supply	Ac 220v, 50Hz; Ac 110v, 60Hz & Ac 230v, 50Hz also available			
20	Material of Panel	alluminium alloy with surface treatment of wire drawing			
21	Modes available				
22	Transistors from TOSHIBA	8 pairs	6 pairs	8 pairs	6 pairs
23	Controlls (front/rear panels)	power,mic stimulate,mic volume, music volume			
24	Net weight( kgs/lbs )	16.5/36.4	15/33.09	11.5/25.37	15/33.09
25	Gross weight( kgs/lbs )				
26	Product size ( mm/in )	485W×435D×135H / 19.09 x 17.13 x 5.31			
27	Package size ( mm/in )	565W×545D×225H / 22.24 x 21.46 x 8.86			
28	pcs/20"FCL/40"FCL/40"HQ	375/779/981	375/779/981	375/779/981	375/779/981