

PART 1 SPECIFICATIONS

	Technical parameters	Technical parameters	Technical parameters	Technical parameters
1	MODEL	S-995	S-993	S-991
2	Rated output power 8Ω	500W×2	400W×2	300W×2
3	Rated output power 4Ω	650W×2	550W×2	400W×2
4	Frequency response	20HZ-20KHZ (-0.5, +0.5dB)		
5	Signal-to-noise ratio	86dB	86dB	82dB
6	Input sensitivity	0.45V	0.42V	0.4V
7	THD	≤0.05%	≤0.05%	≤0.05%
8	Input impedance	20KΩ	20KΩ	20KΩ
9	Supply power	1200W	800W	650W
10	Exchange insurance	10A	8A	8A
	Construction description	Construction description	Construction description	Construction description
11	Rack space	3U	3U	3U
12	Output circuitry	Class AB	Class AB	Class AB
13	Input Connectors	RCA	RCA	RCA
14	Link Connectors			
15	Output Connectors	binding post	binding post	binding post
16	Cooling	constant speed	constant speed	constant speed
17	Indicators	power supply,	power supply,	power supply,
18	Protection	short-circuit,DC voltage, thermal, over-load, limiter		
19	Power Supply	Ac 220v, 50Hz; Ac 110v, 60Hz & Ac 230v, 50Hz also available		
20	Material of Panel	ferrite	ferrite	ferrite
21	Modes available			
22	Transistors from TOSHIBA	10 pairs	8 pairs	6 pairs
23	Controlls (front/rear panels)	gains, mic volume, music volume,input selectors,audio process modes		
24	Net weight(kgs/lbs)	17.5 /38.61	16.5/36.4	14.5/32
25	Gross weight(kgs/lbs)			
26	Product size (mm/in)	430W×340D×135H / 16.93 x 13.39 / 5.3.1	430W×340D×135H / 16.93 x 13.39 / 5.3.1	430W×340D×135H / 16.93 x 13.39 / 5.3.1
27	Package size (mm/in)	500W×440D×180H / 19.69 x 17.32 x 7.09	500W×440D×180H / 19.69 x 17.32 x 7.09	500W×440D×180H / 19.69 x 17.32 x 7.09
28	pcs/20"FCL/40"FCL/40"HQ	656/1257/1257	656/1333/1333	656/1363/1517