

PART 1 SPECIFICATIONS

Technical parameters		Technical parameters
1	MODEL	S-576
2	Rated output power 8Ω	220W×2
3	Rated output power 4Ω	350W×2
4	Frequency response	20HZ-20KHZ (+0.5, +3dB)
5	Signal-to-noise ratio	86dB
6	Input sensitivity	0.24V
7	THD	≤0.05%
8	Input impedance	20KΩ
9	Supply power	500W
10	Exchange insurance	5A
Construction description		Construction description
11	Rack space	3U
12	Output circuitry	Class AB
13	Input Connectors	RCA
14	Link Connectors	
15	Output Connectors	binding post
16	Cooling	constant speed
17	Indicators	input selector,L/R channels volume
18	Protection	short-circuit,DC voltage
19	Power Supply	Ac 220v, 50Hz; Ac 110v, 60Hz & Ac 230v, 50Hz also available
20	Material of Panel	alluminium alloy with surface treatment of wire drawing
21	Modes available	
22	Transistors from TOSHIBA	4 pairs
23	Controlls (front/rear panels)	front:power,echo volume,mic volume. music volume
24	Net weight(kgs/lbs)	9.5/ 20.96
25	Gross weight(kgs/lbs)	
26	Product size (mm/in)	430W×340D×135H / 16.93 x 13.39 x 5.31
27	Package size (mm/in)	500W×440D×180H / 19.69 x 17.32 x 7.09
28	pcs/20"FCL/40"FCL/40"HQ	656/ 1363 / 1717