

PART 1 SPECIFICATIONS

Technical parameters	Technical parameters:	Technical parameters:	Technical parameters:
Item No.	JT-15	JT-12	VC-10
System Type	2-way full range	2-way full range	2-way full range
Frequency Response (±3 dB)	50- 18k Hz	55- 18k Hz	62- 18k Hz
Nominal Impedance	8 Ω	8 Ω	8 Ω
System sensitivity	97 dB	95 dB	98 dB
Power Rating (Continuous)	500 W	250 W	300 W
Power Rating (Peak)	2000W	1000W	1200W
Maximum SPL	130 dB	125 dB	129 dB
Coverage Pattern	75°x50°	75°x50°	90°x50°
Crossover Mode	internal crossover	internal crossover	internal crossover
Product Features	Product Features:	Product Features:	Product Features:
HF Driver	2" x1, copper compression magnet Ø120mm / 4.8 in; voice coil Ø51 mm/2.04 in	2" x1, copper compression magnet Ø120mm / 4.8 in; voice coil Ø51 mm / 2.04 in	2" x1, copper compression magnet Ø100mm / 4 in;voice coil Ø44 mm / 1.76 in of Flat aluminium
MF Driver	—	—	—
LF Driver	15" x1, ferrite magnet Ø190mm / 7.6 in; voice coil Ø75 mm / 3 in made of aluminium wire;aluminium frame	15" x1, ferrite magnet Ø190mm / 7.6 in; voice coil Ø75 mm / 3 in made of aluminium wire;aluminium frame	10" x1, ferrite magnet Ø170mm / 6.8 in; voice coil Ø65 mm / 2.6 in made of aluminium wire; aluminium frame
Input Connectors	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2
Output Connectors	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2
Enclosure	18mm MDF	18mm MDF	15mm Birch plywood
Grille	ferrite,foam backing	ferrite,foam backing	ferrite,foam backing
Finish	Black catalyzed polyurethane paint	Black catalyzed polyurethane paint	Black catalyzed polyurethane paint
Suspension / Mounting	multiple-point suspension/stands to be rotatable	multiple-point suspension/stands to be rotatable	multiple-point suspension/stands to be rotatable
Colour	black	black	black
Product Dimensions(mm,inch)	472W×445D×782H /18.88x 17.8 x31.28 in	345W×540D×300H /18.2 x 18.6 x23.6 in	350W×320 D×500 H /14x 12.8 x20 in
Package Dimensions(mm,inch)	545W×510D×845H /21.8x 20.4x 33.8 in	405W×570D×360H /22x 21.68x 27 in	422W×390 D×577 H /16.88x 15.6x 23.08 in
Net Weight(kgs,lbs)	37KGS/ 81.63 lbs	20KGS/ 81.63 lbs	14.5 KGS/ 31.99 lbs
Gross Weight(kgs,lbs)	39KGS/ 86.05 lbs	39KGS/ 86.05 lbs	16.5 KGS/ 36.4 lbs
Optional Accessories	aluminium alloy suspension fittings	aluminium alloy suspension fittings	aluminium alloy suspension fittings
Package Rate(pc/carton)			
PCS/20" FCL/40"FCL/40"HQ	123/246/323	348/697/914	305/610/800
Operating the System	Operating the System:	Operating the System:	Operating the System:
Recommended Amplification	600 - 750 Watt @8 ohms 1 x amplifier	500 - 600 Watt @8 ohms 1 x amplifier	350 - 450 Watt @8 ohms 1 x amplifier
Subwoofer Options			
System Controller			
Speaker Cables			