

**PART 1 SPECIFICATIONS**

Technical parameters	Technical parameters:	Technical parameters:
Item No.	<b>B-218</b>	<b>F-55B</b>
System Type	Ultra-low Sub bass,passive	Ultra-low Sub bass,active
Frequency Response (±3 dB)	28- 400 Hz	40-150 Hz
Nominal Impedance	4 Ω	4 Ω
System sensitivity	105 dB	700 mv
Power Rating (Continuous)	1600 W	300 W
Power Rating ( Peak)	6400W	—
Maximum SPL	143 dB	129 dB
Coverage Pattern	48°x50°	48°x50°
Crossover Mode	external crossover	internal crossover
Product Features	Product Features:	Product Features:
HF Driver	—	—
MF Driver	—	—
LF Driver	18" x2, ferrite magnet Ø220 mm / 8.8 in; voice coil Ø100 mm / 4 in made of aluminium wire; high density cast aluminium frame	15" x1, ferrite magnet Ø190 mm / 7.6 in; voice coil Ø75 mm / 3 in made of aluminium wire; cast aluminium frame
Input Connectors	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2
Output Connectors	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2
Enclosure	18mm Birch plywood	18mm MDF
Grille	ferrite,foam backing	ferrite,foam backing
Finish	Black catalyzed polyurethane paint	Black catalyzed polyurethane paint
Suspension / Mounting	reserved 4 installing holes in the back for 4	
Colour	black	black
Product Dimensions(mm,inch)	1160W×920 D×580 H /46.4x 36.8 x23.2 in	533W×560 D×603. H /21.32x 22.4 x24.12 in
Package Dimensions(mm,inch)	1215W×970 D×637 H /48.6x 38.8x 25.48 in	622W× D580 HX 655 /24.88x 23.2x 26.2 in
Net Weight(kgs,lbs)	100 KGS/ 220.63 lbs	45.5 KGS/ 100.39 lbs
Gross Weight(kgs,lbs)	108 KGS/ 238.23 lbs	48 KGS/ 105.9 lbs
Optional Accessories		
Package Rate(pc/carton)		
PCS/20" FCL/40"FCL/40"HQ	38/77/101	122/245/321
Operating the System	Operating the System:	Operating the System:
Recommended Amplification	2000 - 2400 Watt @4 ohms 1 x amplifier	2000 - 2400 Watt @4 ohms 1 x amplifier
Subwoofer Options		
System Controller		
Speaker Cables		