

PART 1 SPECIFICATIONS

Technical parameters	Technical parameters:
Item No.	PRX-625
System Type	2-WAY full range
Frequency Response (±3 dB)	40Hz-18k Hz
Nominal Impedance	4 Ω
System sensitivity	103 dB
Power Rating (Continuous)	1200 W
Power Rating (Peak)	4800W
Maximum SPL	140 dB
Coverage Pattern	70x50o
Crossover Mode	internal crossover
Product Features	Product Features:
HF Driver	3" x1, ferrite magnet Ø170mm/6.8 in; voice coil Ø7 mm/3 in of FCCA wire; cast aluminium frame; aluminium rear panel; rectangular horn of FRP
MF Driver	—
LF Driver	15" x2, ferrite magnet Ø190mm / 7.6 in; voice coil Ø75 mm / 3 in made of flat copper wire
Input Connectors	NL4speakon(x2) NL4socketx2
Output Connectors	NL4speakon(x2) NL4socketx2
Enclosure	18mm MDF or 18mm birch plywood
Grille	ferrite
Finish	Black catalyzed polyurethane paint
Suspension / Mounting	multiple-point suspension
Colour	black
Product Dimensions(mm,inch)	485W×510D×1140H / 19.4 x 20.4 x 45.6 in
Package Dimensions(mm,inch)	577W×600D×1235H / 23.01x 24 x 49.4 in
Net Weight(kgs,lbs)	52 KGS/ 114.73 lbs
Gross Weight(kgs,lbs)	
Optional Accessories	aluminium alloy suspension fittings
Package Rate(pc/carton)	
PCS/20" FCL/40"FCL/40"HQ	67/135/177
Operating the System	Operating the System:
Recommended Amplification	1450 - 1800 Watt @ 4 ohms 1 x amplifier
Subwoofer Options	
System Controller	
Speaker Cables	