

PART 1 SPECIFICATIONS

	Technical parameters	Technical parameters	Technical parameters
1	MODEL	S-775	S-770
2	Rated output power 8Ω	250W×2	160W×2
3	Rated output power 4Ω	400W×2	250W×2
4	Frequency response	20HZ-20KHZ (-1, +2dB)	20HZ-20KHZ (-1, +2dB)
5	Signal-to-noise ratio	84dB	82.5dB
6	Input sensitivity	0.24V	0.21V
7	THD	≤0.05%	≤0.05%
8	Input impedance	20KΩ	20KΩ
9	Supply power	600W	400W
10	Exchange insurance	5A	3A
	Construction description	Construction description	Construction description
11	Rack space	3U	3U
12	Output circuitry	Class AB	Class AB
13	Input Connectors	RCA	RCA
14	Link Connectors		
15	Output Connectors	binding post	binding post
16	Cooling	constant speed	constant speed
17	Indicators	input selector,L/R channels volume	input selector,L/R channels volume
18	Protection	short circuit, DEvoltage,	short circuit, DEvoltage,
19	Power Supply	Ac 220v, 50Hz; Ac 110v, 60Hz & Ac 230v, 50Hz also available	Ac 220v, 50Hz; Ac 110v, 60Hz & Ac 230v, 50Hz also available
20	Material of Panel	alluminium alloy with surface treatment of wire drawing	alluminium alloy with surface treatment of wire drawing
21	Modes available		
22	Transistors from TOSHIBA	4 pairs	2 pairs
23	Controlls (front/rear panels)	front: power,input selecter,mic volume, music volume	front: power,input selecter,mic volume, music volume
24	Net weight(kgs/lbs)	10/22.06	8.5/17.65
25	Gross weight(kgs/lbs)		
26	Product size (mm/in)	430W×340D×135H / 16.93 x 13.39 x 5.31	430W×340D×135H / 16.93 x 13.39 x 5.31
27	Package size (mm/in)	500W×440D×180H / 19.69 x 17.32 x 7.09	500W×440D×180H / 19.69 x 17.32 x 7.09
28	pcs/20"FCL/40"FCL/40"HQ	656/ 1363 / 1717	656/ 1363 / 1717