

PART 1 SPECIFICATIONS

Technical parameters	Technical parameters	Technical parameters
Item No.	L-8	L-8A
System Type	2-way, linear array full range	linear array ,mono 15" sub-bass
Frequency Response (±3 dB)	120Hz-18KHz	55Hz-400Hz
Nominal Impedance	16 Ω	8 Ω
System sensitivity	95 dB	100 dB
Power Rating (Continuous)	300 W	500 W
Power Rating (Peak)	1200W	2000W
Maximum SPL	126 dB	133 dB
Coverage Pattern	—	—
Crossover Mode	inside/outside crossovers,extremely	outside crossover
Product Features	Product Features	Product Features
HF Driver	2" x1,44mm(1.76 in) voice coil,aluminium frame	
MF Driver	—	—
LF Driver	8" x2,50mm(2 in) voice coil,	15" x1,voice coil Ø100mm(4 in)
Input Connectors	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2
Output Connectors	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2
Enclosure	hi-strength 15mm Birch Plywood	hi-strength 15mm Birch Plywood
Grille	ferrite	ferrite
Finish	Black catalyzed polyurethane paint	Black catalyzed polyurethane paint
Suspension / Mounting	linear suspention	linear suspention
Colour	black	black
Product Dimensions(mm,inch)	490W×455D×145H /19.6 x 18.2 x 5.8 in	750W×501D×470H /30 x 20.04x 18.8 in
Package Dimensions(mm,inch)	575W×560D×200H /23 x 22.4 x 8 in	810W×550D×535H /32.4x 22 x 21.4 in
Net Weight(kgs,lbs)	22.3 KGS / 49.2 lbs	42.8 KGS/ 94.4 lbs
Gross Weight(kgs,lbs)		
Optional Accessories	aluminium alloy suspension fittings	aluminium alloy suspension fittings
Package Rate(pc/carton)		
PCS/20" FCL/40"FCL/40"HQ	450/900/1180	121/243/318
Operating the System	Operating the System	Operating the System
Recommended Amplification	300 - 450 Watt @ 16 ohms 1 x amplifier	600 - 750 Watt @ 8 ohms 1 x amplifier
Subwoofer Options		
System Controller		
Speaker Cables		