

**PART 1 SPECIFICATIONS**

Technical parameters	Technical parameters	Technical parameters
Item No.	<b>L-10</b>	<b>L-12</b>
System Type	linear array, 2-way full range	linear array , 3-way full range
Frequency Response (±3 dB)	45Hz-18kHz	40Hz-18 kHz
Nominal Impedance	16 Ω	16 Ω
System sensitivity	97 dB	100 dB
Power Rating (Continuous)	600 W	1000 W
Power Rating ( Peak)	2400W	4000W
Maximum SPL	131 dB	136 dB
Coverage Pattern	—	—
Crossover Mode	inside / outside crossovers	inside / outside crossovers
<b>Product Features</b>	<b>Product Features</b>	<b>Product Features</b>
HF Driver	3" x1, voice coil Ø100mm(4 in)	2" x2, voice coil Ø100mm(4 in)
MF Driver	—	6" x4, voice coil Ø100mm(4 in)
LF Driver	10" x2,voice coil Ø100mm(4 in)	12" x2, voice coil Ø100mm(4 in)
Input Connectors	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2
Output Connectors	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2
Enclosure	hi-strength 15mm Birch Plywood	hi-strength 15mm Birch Plywood
Grille	ferrite	ferrite
Finish	Black catalyzed polyurethane paint	Black catalyzed polyurethane paint
Suspension / Mounting	linear suspention	linear suspention
Colour	black	black
Product Dimensions(mm,inch)	900W×505D×370H /36 x 20.2x 14.8 in	1125W×563D×425H /45 x 22.52x 17 in
Package Dimensions(mm,inch)	960W×565D×590H /38.4x 22.6 x 23.6 in	1195W×625D×630H /47.8 x 25 x 25.2 in
Net Weight(kgs,lbs)	41.7 KGS/ 92 lbs	75.6 KGS/ 167.2 lbs
Gross Weight(kgs,lbs)		
Optional Accessories	aluminium alloy suspension fittings	aluminium alloy suspension fittings
Package Rate(pc/carton)		
PCS/20" FCL/40"FCL/40"HQ	90 / 181 / 237	61 / 123 / 161
<b>Operating the System</b>	<b>Operating the System</b>	<b>Operating the System</b>
Recommended Amplification	720 - 900 Watt @ 16 ohms 1 x amplifier	1200 - 1500 Watt @ 16 ohms 1 x amplifier
Subwoofer Options		
System Controller		
Speaker Cables		