

**PART 1 SPECIFICATIONS**

Technical parameters	Technical parameters:	Technical parameters:
Item No.	<b>H-5A</b>	<b>H-5B</b>
System Type	passive ULF	2-WAY full range
Frequency Response (±3 dB)	30Hz-1.2k Hz	1200Hz-20k Hz
Nominal Impedance	8 Ω	8 Ω
System sensitivity	99 dB	101 dB
Power Rating (Continuous)	500 W	400 W
Power Rating ( Peak)	2000W	1600W
Maximum SPL	126 dB	127 dB
Coverage Pattern		
Crossover Mode	internal / external crossover	internal / external crossover
<b>Product Features</b>	<b>Product Features:</b>	<b>Product Features:</b>
HF Driver	—	3" x1,ferrite magnet Ø190mm /7.6in;
MF Driver	—	50" x1,ferrite magnet Ø170mm/6.8in;
LF Driver	15" x1,ferrite magnet Ø220mm/ 8.8in;	—
Input Connectors	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2
Output Connectors	NL4speakon(x2) NL4socketx2	NL4speakon(x2) NL4socketx2
Enclosure	18mm Birch Plywood	18mm Birch Plywood
Grille	ferrite	ferrite
Finish	Black catalyzed polyurethane paint	Black catalyzed polyurethane paint
Suspension / Mounting	superposing	superposing
Colour	black	black
Product Dimensions(mm,inch)	610W×636D×660H /24.4 x 25.44 x 26.4 in	610W×636D×580H /24.4 x 25.44 x 23.2 in
Package Dimensions(mm,inch)	726W×702D×757H /30.64x 28.08 x 30.28 in	726W×702D×677H /30.64x 28.08 x 27.08 in
Net Weight(kgs,lbs)	46 KGS/ 101.5 lbs	42.5 KGS/ 94.4 lbs
Gross Weight(kgs,lbs)		
Optional Accessories	aluminium alloy suspension fittings	aluminium alloy suspension fittings
Package Rate(pc/carton)		
PCS/20" FCL/40"FCL/40"HQ	75/150/196	75/150/196
<b>Operating the System</b>	<b>Operating the System:</b>	<b>Operating the System:</b>
Recommended Amplification	600 - 750 Watt @ 8 ohms 1 x amplifier	400 - 600 Watt @ 8 ohms 1 x amplifier
Subwoofer Options	—	
System Controller	—	
Speaker Cables		